

Prestige 630-C Series ADSL USB Modem



- Models:**
- Prestige 630-C1
ADSL USB Modem over POTS
 - Prestige 630-C3/C7
ADSL USB Modem over ISDN/U-R2

ZyXEL's Prestige 630-C series modem makes ADSL more accessible than ever. With the convenience of a Universal Serial Bus (USB) interface, the Prestige 630-C series DSL modem can be effortlessly deployed without the hassle of installing Network Interface Cards (NICs) on a user's computer. Moreover, the Prestige 630-C series is USB Bus-Powered and requires no external power adaptor, further simplifying deployment.

With the greater data throughput rates achieved by high-speed Internet access, applications such as web browsing, interactive gaming, and streaming multimedia are becoming virtually instantaneous. Powerful downstream rates of up to 8Mbps make the Prestige 630-C series perfect for bandwidth-demanding Internet surfers.

To enhance efficiency, ZyXEL provides flexible chipset solutions to ensure maximum interoperability with major DSLAMs.

Benefits

High Speed Internet Access


The Prestige 630-C series is capable of supporting downstream transmission rates of up to 8Mbps and upstream rates of up to 1024Kbps.

Easy to Install

The software installation process of the Prestige 630-C series is extremely easy. The automatic setup wizard completes the whole process in just a few steps.

Easy to Deploy

The USB-Bus powered Prestige 630-C series does not require an external power adaptor. The compact size and convenient installation process makes set up quick and easy.



Features & Specifications

- No external power adaptor is required
- USB 1.1 interface, compatible with USB 2.0 root hubs
- ADSL compliance
 - Multi-Mode ADSL Standard
 - Speed up to 8Mbps downstream, 1024Kbps upstream
 - ANSI T1.413 Issue 2
 - ITU G.dmt (G.992.1 Annex A, Annex B and U-R2)
 - ITU G.Lite (G.992.2)
 - ITU G.hs (G.994.1)
 - Auto-negotiating Rate Adaptation
- OS Support
 - Win98SE, Win2000, WinME, WinXP
 - Mac OS9, X (Option)
- ATM Protocol
 - Bridged (Multi-protocol over AAL5 ATM, RFC 1483/2684)
 - PPPoE (PPP over Ethernet, RFC2516)
- PPPoA (PPP over ATM AAL5, RFC 2364)
- Classical IPoA (Classical IP over ATM, RFC 1577/2225)
- Support VC and LLC based multiplexing QoS support AAL5 UBR, CBR
- ITU-T I.610 OAM F4/F5
- Support dying GASP
- Support suspend function
- Software upgradeable
- Web-based configuration supported for LAN, WAN, and ADSL setting (Option)
- WAN Interface
 - One RJ-11 for Annex A, Prestige 630-C1 over POTS
 - One RJ-45 port for Annex B, U-R2, P630-C3/C7 over ISDN/U-R2
- LAN Interface: One USB port
- Status LED Indicator: DSL, USB
- Power: USB Bus-Powered (4.75V DC ~ 5.25V DC)
- Dimensions: 109 (L) x 105 (D) x 22 (H) mm
- Weight: 146g
- Operation Environment
 - Temperature: 0 ~ 50°C
 - Humidity: 20% ~ 85%
- Storage Environment
 - Temperature: -30 ~ 60°C
 - Humidity: 20% ~ 90%
- Optional Parts
 - Micro filter
 - POTS splitter
- Warranty: 2 Years
- System Requirement
 - Pentium II 233 or above
 - OS: Win98SE, Win2000, WinME, WinXP, Mac (Option)
 - Memory size: 32MB (64MB recommended)
 - Hard Disk: 10 MB



Corporate Headquarters
ZyXEL Communications Co.
Tel: +886-3-578-3942
Fax: +886-3-578-2439
Email: sales@zyxel.com.tw
http://www.zyxel.com
http://www.zyxel.com.tw

North America
ZyXEL Communications Inc.
Tel: +1-800-255-4101
Email: sales@zyxel.com
http://www.us.zyxel.com

Germany
ZyXEL Deutschland GmbH.
Tel: +49 2405 6909 0
Fax: +49 2405 6909 99
Email: sales@zyxel.de
http://www.zyxel.de

Denmark
ZyXEL Communications A/S
Tel: +45 39 55 07 00
Fax: +45 39 55 07 07
Email: sales@zyxel.dk
http://www.zyxel.dk

Norway
ZyXEL Communications A/S
Tel: +47 22 80 61 80
Fax: +47 22 80 61 81
Email: sales@zyxel.no
http://www.zyxel.no

Sweden
ZyXEL Communications A/S
Tel: +46 31 744 7700
Fax: +46 31 744 7701
Email: sales@zyxel.se
http://www.zyxel.se

Finland
ZyXEL Communications Oy
Tel: +358-9-4780 8400
Fax: +358-9-4780 8448
Email: sales@zyxel.fi
http://www.zyxel.fi